

Dynamic Cargo Securing

Dynamic shipping challenges are unique because cargo can be intrinsically dynamic and even static cargo can behave dynamically when exposed to outside forces. That is why Cordstrap's Dynamic Cargo Securing solution utilizes our patented grooved Dynablock buckle and our industry leading Cordlash product, to create a single flexible solution that is superior to steel based securing products such as cable and chain as well as polyester ratchet systems. So whether it's intrinsically dynamic cargo, or static cargo that behaves dynamically, the Cordstrap Dynamic Cargo Securing solution provides unparalleled safety and security in one innovative and efficient system.

Benefits

One Integrated Solution

A solution utilizing proven one-way polyester lashing. Works on intrinsically dynamic cargo, static cargo that behaves dynamically and static cargo. Applicable to both open en closed CTU's.

Effective and Efficient

Effectively absorbs vibrations during transport and prevents slippage in all dynamic situations. As strong as steel yet won't damage cargo.

Safe and Flexible

Safer to work with than steel, cable or chains. Customizable strap length reduces wastage. Easy to apply in any situation.



Features



Unique patented Dynablock buckle with grooves, prevents lashing from slipping



Flexible one-way polyester lashing does not damage cargo or equipment



A safe, quick and easy way to secure cargo of any shape and size



GL witnessed.

AAR approved,
compliant with
DIN(EN) and
ASTM standards





Dynamic Cargo Securing Specifications									
Lashing	Cordlash 95	Cordlash 105	Cordlash 150	Cordlash 200	Cordlash 750	Cordlash 1500			
Buckle	Dynablock 10	Dynablock 10	Dynablock 12 - 150	Dynablock 12 - 200	Dynablock 15	Dynablock 20			
Recommended Tensioners	CT35PN CT40 (2) CTT40	CT35PN CT40 (2) CTT40	CT40PN CT40 (2) CTT40	CT40PN CRT50	CT60PN CRT50	CT60PN CRT60			
System Breaking Strength	3500 daN 7870 lbf	4000 daN 9000 lbf	6000 daN 13500 lbf	8500 daN 19100 lbf	12000 daN 22500 lbf	20000 daN 44000 lbf			
MSL Value (USA - WLL)	1750 daN 3935 lbf	2000 daN 3000 lbf	3000 daN 6750 lbf	4250 daN 9950 lbf	6000 daN 11250 lbf	10000 daN 22000 lbf			
AAR Grade	5	5	6	7	8				
German Lloyd Witnessed	√	1	1	1	✓	✓			

Dynablock® Specifications										
	Dynablock	Dynablock	Dynablock	Dynablock	Dynablock	Dynablock				
	10	12 - 150	12 - 200	15	20	Hook 12				
Width	32 mm	40 mm	40 mm	50 mm	60 mm	40 mm				
	1.1/4"	1.5/8"	1.5/8"	2"	2.3/8"	1.5/8"				
Dimensions*	132 x 57 x 17mm	132 x 66 x 17 mm	132 x 72 x 17 mm	132 x 86 x 17mm	212 x 80 x 40 mm	175 x 70 x 50 mm				
	5.1/6 x 2.1/4	5.1/6 x 2.1/3	5.1/6 x 2.5/6	5.1/6 x 3.1/3	8.1/3 x 35/32	6.5/6 x 2.3/4				
	x 43/64"	x 43/64"	x 43/64"	x 43/64"	x 43/64"	x 2"				
Weight	0.5 kg	0.6 kg	0.7 kg	0.8 kg	2.3 kg	0.6 kg				
per piece	1,1 lbs	1,3 lbs	1,5 lbs	1,8 lbs	5,1 lbs	1,3 lbs				
Pieces per box	20	20	20	20	6	20				

^{*}Tolerance of +/- 5%

All information provided is based on accuracy at time of creation



Represented in over 50 countries
World market leader
ISO 9001:2008 certified

Manufacturer & supplier since 1965
Offering genuine customer solutions

Specialist advice
Continued product development
Training at Cordstrap Training Centers
Quality assurance