

Cordstrap


CornerLash® AAR

Specifically designed for heavy loads in containers, CornerLash® is a breakthrough innovation in cargo securing. The most time and cost efficient solution on the market, CornerLash® enables heavy cargo (up to 30 tons) to be secured in an easy and consistent way.

Suitable for many types of heavy loads, from drums, big bags, IBC's, 25kg / 50 lb bags and other and other soft packaging – in both 20 ft and 40 ft containers – the CornerLash® solution ensures cargo is secured in the safest and most efficient way possible. 'Plug and Play' components – including load specific add-ons such as engineered protectors for IBC's and EdgeBoards specially designed for soft packaging – ensure enhanced safety and speed.

Complying fully with the latest rules and regulations, CornerLash® supports your responsibilities as a shipper, ensuring your cargo gets through port controls smoothly and arrives at its destination safely and in perfect condition.

Cordstrap CornerLash® protects your cargo, your people and your brand.



Optimal Security

CornerLash® utilizes the strongest part of the container – the corner posts – to provide optimal security for heavy loads of up to 30 tons in transit, through the use of our innovative, patented corner element.



Fast and Easy Application

Securing a container with CornerLash® takes only ten minutes. 'Plug and Play' components including cut-to-length lashing mean no excessive preparation or tidying up are required.



Fully Certified

CornerLash® is AAR approved and carries Lloyds and MariTerm CTU Code compliance/certification and Eurosafe certification.



Expert Support

CornerLash® is fully supported by training and implementation from local cargo securing experts, enabling standardization and consistency.



Specifications Cordstrap Container Solution **Solution Performance Specifications** Cordstrap CornerLash® AAR CornerLash® Specification لسا System Breaking Strength 12.000 daN / 26,400 lbf 6.000 daN / 13,200 lbf 1 System Solution Breaking Strength 24.000 daN / 52,800 lbf ┖╓╖┦ Elongation at MSL <5.5% Required pre-tension 3.000 daN / 6,600 lbf Recommended pre-tension Certification AAR approved, Lloyd's and MariTerm CTU Code Compliant certified 1 Solution Eurosafe Certified Corner Element Specification **Breaking Strength** 6.000 daN / 13,200 lbf 3.000 daN / 6,600 lbf MSL

Edge protection and HangStrap: used to keep the lashing in an optimal position and fully protect your cargo

Galvanized Steel



Pieces required per solution

Material

EdgeBoards (soft packaging)



FlexBoards (drums and big bags)



IBC Protector



HangStrap

Use the recommended tools to enable easy, fast and consistent application $% \left(1\right) =\left(1\right) \left(1\right)$



CornerLash® Application Tool



CRT50



Pneumatic Tensioner CT50 PN



C11 Battery Operated Tool



Container Magnets

Loading plans



